

$\phi 28 \text{ h}8_{-0.03}$
Clamping diameter

105.17

47.72

43.52

32.92

29.22

20.22

0

4.30

$\phi 37.60$


$\phi 45$

F-Mount
Flange distance 46.5

$\phi 64$

Phase
adjustment

$\phi 20$
Clear
aperture

Material		N.A.		Mass		331 g		Scale		1.5:1							
Surface treatment				Part No.		CO31976											
Geometrical tolerance (ISO 2768-2)								Class		K							
Linear tolerance (ISO 2768-2)								Class		m							
0.5 ±3	>3± 6	>6± 30	>30± 120	>120 ±400	>400± 1000	>1000 ±2000	>2000 ±4000	Undimensioned bevels	0.5x45°								
±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	Undimensioned radii	R 0.5								
 <p>OPTO ENGINEERING</p>								Date		Name		Drawing No.		Sheet			
								Designed		21/03/2022		Ccharly		DP 31976-A		1/1	
								Drawn		31/03/2022		Ccharly					
Checked		11/05/2022		Rizzotto		<i>Secret and confidential - All rights reserved - No copy, dissemination or circulation is allowed unless specifically authorized in writing by OPTO ENGINEERING S.p.A. - Any violation shall be legally prosecuted.</i>											
OPTO ENGINEERING S.p.A. - Mantova, Italy - Tel. +39 0376699111 - www.opto-e.com																	

all dimensions are in mm