

Four Compact $\phi 43\text{mm}$ Machine-Vision Lenses Compatible with 1.1" Imagers and Full 24-Mega Pixel Resolution

- 1.1" 16mm F/2.8 (Model: MA111F16VIR)
- 1.1" 25mm F/2.8 (Model: MA111F25VIR)
- 1.1" 35mm F/2.8 (Model: MA111F35VIR)
- 1.1" 50mm F/2.8 (Model: MA111F50VIR)



For

IMX253 1.1" 12-Mega

IMX304 1.1" 12-Mega

IMX532 1.1" 16-Mega

IMX542 1.1" 16-Mega

IMX531 1.1" 20-Mega

IMX541 1.1" 20-Mega

2.5 μm

※24-Mega(max)pixel resolution

Main Features

> High Resolution and Contrast Unrivaled in the Industry

- Compatible with 1.1" imagers, supporting 2.5 μm pixel-pitch and 24-mega* (max) pixel resolution.
- Offer resolution and contrast outperforming other 24-mega pixel lenses.
(* resolution at the center)

> Industry-Leading Low Distortion (TV Distortion)

- Significantly reduce TV Distortion compared with previous models.
(* MA111F16VIR: 0.2%, MA111F25VIR: -0.3%, MA111F35VIR: 0.3%, MA111F50VIR: 0.1%)

> High-Quality Performance from Close-up to Infinity

- A new comprehensive lens design covering both close-up and infinity shooting distances assures high contrast and resolution throughout the whole focal length range.





> New Robust Mechanism for Anti-Vibration and Anti-Shock

- A newly designed mechanism improves anti-vibration and anti-shock performance compared with previous models, limiting the optical (image) deflection to less than 10 μm even for the severe impact of vibrations and shocks of max 10G of magnitude.
*Vibration frequency 10-150Hz (acceleration 50m/s²), and the number of cycles: 20 cycles.

> Reduction of Focus-Shift in between the Visible-Light and the NIR Bands

- Focus-shift associated with the wide spectrum of 400nm to 850nm is reduced to an absolute minimum, which makes the new lenses an optimum choice for cameras compatible with the visible-light and the NIR band.

■ Specifications

| Model | MA111F16VIR | MA111F25VIR | MA111F35VIR | MA111F50VIR |
|--|---|---|---|---|
| |  |  |  |  |
| Imager Size | 1.1" | | | |
| Mount Type | C | | | |
| Focal Length | 16mm | 25mm | 35mm | 50mm |
| Aperture Range | F/2.8 ~ F/16 | | | |
| Field of View Angle (Horizontal x Vertical) | 1.1" | 47.7°x36.8° | 31.7°x23.9° | 22.8°x17.2° |
| | 2/3" | 30.8°x23.3° | 20.0°x15.0° | 14.4°x10.8° |
| Focusing Range | 0.1m ~ ∞ | | 0.2m ~ ∞ | |
| Operation | Focus | Manual w/lock | | |
| | Iris | Manual w/lock | | |
| Filter Size | M40.5 P=0.5mm | | | |
| Wave Length | Visible Light~NIR | | | |
| TV Distortion | 0.2% * | -0.3% * | 0.3% * | 0.1% * |
| Weight | 178g | 196g | 179g | 181g |
| Operating Temperature | -20°C ~ +60°C | | | |

* Design Value

TAMRON CO., LTD. <http://www.tamron.biz/en/>
1385, Hasunuma, Minuma-ku, Saitama-shi, Saitama 337-8556 JAPAN
Tel: +81-48-684-9129 Fax: +81-48-683-8594

TAMRON USA, INC. <http://www.tamron-usa.com>
10 Austin Boulevard, Commack, NY 11725, USA Tel: +1-631-858-8400 Fax: +1-631-543-3963

TAMRON Europe GmbH. <http://www.tamron.de>
Robert Bosch-Str. 9, 50769 Cologne, GERMANY Tel: +49-221-669544-0 Fax: +49-221-669544-404

TAMRON INDUSTRIES (HONG KONG) LIMITED <http://www.tamron.com.hk>
Unit 908, 9/F, Elite Centre, 22 Hung To Road, Kwun Tong, Kowloon, Hong Kong Tel: +852-2721-7797 Fax: +852-2620-1631

TAMRON (Russia) LLC. <http://www.tamron.ru>
Unikon Business Center 5F No. 9, Plekhanova Street 4a, Moscow, 111123, Russian Federation
Tel: +7-495-970-0112 Fax: +7-495-970-0112

TAMRON OPTICAL (SHANGHAI) CO., LTD. <http://www.tamron.com.cn>
Room 1707, Ruijin Building, No.205, Maoming South Road, Shanghai, 200020, CHINA
Tel: +86-21-5102-8880

TAMRON INDIA PRIVATE LIMITED <http://www.tamron.in>
805, 806 & 807 8th floor, Vatika City Point, MG Road, Gurgaon-122001, Hayana, India
Tel: +91-124-41-168-12 Fax: +91-124-40-822-72



Management on Quality and Environment :

Tamron is certified with international standards: ISO 9001 for quality and ISO 14001 for environmental management at its Head Office, domestic sales offices, China plant as well as production facilities in Aomori Factory, Japan, and is fully committed to striving for continued and sustainable improvement at all levels and facets of its business operations.

● Specifications subject to change without notice